



## SAFETY DATA SHEET AP Pump Saver 195

---

### SECTION 1. Identification

#### Product identifier

Product name AP Pump Saver 195

#### Recommended use of the chemical and restrictions on use

Recommended use: Hydraulic Oil Booster & Stop Leak  
Restrictions on use: All others.

#### Supplier's details

Name Alchemy-Spetec  
Address 4508 Bibb Blvd  
Tucker GA 30084  
Telephone (404) 618-0438

#### Emergency phone number(s)

Call CHEMTREC Day or Night  
1-800-424-9300 / +1 703-527-3887

---

### SECTION 2. Hazard(s) identification

#### Lucas Oil Additive

#### OSHA/HCS status:

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

#### Classification of the substance or mixture:

Not classified.

#### GHS label elements

##### Signal word:

No signal word.

##### Hazard statements:

No known significant effects or critical hazards.

#### Precautionary statements

##### General:

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

##### Prevention:

Not applicable.

##### Response:

Not applicable.

# Safety Data Sheet

## AP Pump Saver 195

**Storage:** Not applicable.

**Disposal:** Not applicable.

**Hazards not otherwise classified:** None known.

### Hydraulic Oil

#### **Classified Hazards**

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

#### **Other Hazards**

None Known

#### **Label Elements:**

No classified hazards

---

## SECTION 3. Composition/information on ingredients

### Lucas Oil Additive

**Substance/mixture:** Substance

**Other means of identification:** Lucas Hydraulic Oil Booster & Stop Leak

#### **CAS number/other identifiers**

**CAS number:** Not available.

**Product code:** 10018, 10019, 20019, 10034, 30019A, 10039, 10040

Ingredient name	%	CAS number
Distillates (petroleum), solvent-refined heavy naphthenic	60 - 100	64741-96-4

**Any concentration shown as a range is to protect confidentiality or is due to batch variation.**

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Hydraulic Oil

Chemical Name	CASRN	Concentration <sup>1</sup>
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	45-86
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0	<37
Non-Hazardous Materials	VARIOUS	<15

<sup>1</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## SECTION 4. First-aid measures

### Lucas Oil Additive

#### Description of necessary first aid measures

<b>Eye contact:</b>	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
<b>Inhalation:</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
<b>Skin contact:</b>	Wash contaminated skin with soap and water. Get medical attention if symptoms occur.
<b>Ingestion:</b>	Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

##### Potential acute health effects

<b>Eye contact:</b>	No known significant effects or critical hazards.
<b>Inhalation:</b>	No known significant effects or critical hazards.
<b>Skin contact:</b>	No known significant effects or critical hazards.
<b>Ingestion:</b>	No known significant effects or critical hazards.

##### Over-exposure signs/symptoms

<b>Eye contact:</b>	No known significant effects or critical hazards.
<b>Inhalation:</b>	No known significant effects or critical hazards.
<b>Skin contact:</b>	No known significant effects or critical hazards.
<b>Ingestion:</b>	No known significant effects or critical hazards.

#### Indication of immediate medical attention and special treatment needed, if necessary

<b>Notes to physician:</b>	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
<b>Specific treatments:</b>	No specific treatment.
<b>Protection of first-aiders:</b>	No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

# Safety Data Sheet

## AP Pump Saver 195

### Hydraulic Oil

<b>Eye Contact:</b>	If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.
<b>Skin Contact:</b>	Remove contaminated shoes and clothing and cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops and persists, seek medical attention. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician. (see Note to Physician)
<b>Inhalation (Breathing):</b>	First aid is not normally required. If breathing difficulties develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. Seek immediate medical attention.
<b>Ingestion (Swallowing):</b>	First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.
<b>Most important symptoms and effects, both acute and delayed:</b>	Inhalation of oil mists or vapors generated at elevated temperatures may cause respiratory irritation. Accidental ingestion can result in minor irritation of the digestive tract, nausea and diarrhea. Dry skin and possible irritation with repeated or prolonged exposure.

**Notes to Physician:** Acute aspirations of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. When using high-pressure equipment, injection of product under the skin can occur. In this case, the casualty should be sent immediately to the hospital. Do not wait for symptoms to develop. High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. These injuries often require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury. Early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

---

## SECTION 5. Fire-fighting measures

### Lucas Oil Additive

#### Extinguishing media

<b>Suitable extinguishing media:</b>	Use an extinguishing agent suitable for the surrounding fire.
<b>Unsuitable extinguishing media:</b>	None known.
<b>Specific hazards arising from the chemical:</b>	No specific fire or explosion hazard.
<b>Hazardous thermal decomposition products:</b>	No specific data.
<b>Special protective actions for fire-fighters:</b>	No special precaution is required.
<b>Special protective equipment for fire-fighters:</b>	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Safety Data Sheet

## AP Pump Saver 195

### Hydraulic Oil

#### NFPA 704 Hazard Class

Health: 0 Flammability: 1 Instability: 0



0 (Minimal)  
(Slight)  
(Moderate)  
(Serious)  
(Severe)

#### Extinguishing Media:

Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F / 100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

#### Specific hazards arising from the chemical

##### Unusual Fire & Explosion Hazards:

This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

##### Hazardous Combustion Products:

Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

##### Special protective actions for firefighters:

For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8).

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

---

## SECTION 6. Accidental release measures

### Lucas Oil Additive

#### Personal precautions, protective equipment and emergency procedures

##### For non-emergency personnel:

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

# Safety Data Sheet

## AP Pump Saver 195

### For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

#### Small spill:

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill:

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Hydraulic Oil

#### Personal precautions, protective equipment and emergency procedures:

This material may burn, but will not ignite readily. Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

#### Environmental Precautions:

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard. Spills into or upon navigable waters, the contiguous zone, or adjoining shorelines that cause a sheen or discoloration on the surface of the water, may require notification of the National Response Center (phone number 800-424-8802).

# Safety Data Sheet

## AP Pump Saver 195

### Methods and material for containment and cleaning up:

Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken. See Section 13 for information on appropriate disposal.

---

## SECTION 7. Handling and storage

### Lucas Oil Additive

#### Precautions for safe handling

##### Protective measures:

Put on appropriate personal protective equipment (see Section 8).

##### Advice on general occupational hygiene:

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

##### Conditions for safe storage, including any incompatibilities:

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

### Hydraulic Oil

#### Precautions for safe handling:

Keep away from flames and hot surfaces. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8). Spills will produce very slippery surfaces. High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns, fuel injection apparatus or from pinhole leaks in tubing of high pressure hydraulic oil equipment.

**Safety Data Sheet  
AP Pump Saver 195**

**Conditions for safe storage:**

Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. Do not wear contaminated clothing or shoes.

Use and store this material in cool, dry, well-ventilated area away from heat and all sources of ignition. Keep container(s) tightly closed and properly labeled. Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1, and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

**SECTION 8. Exposure controls/personal protection**

**Lucas Oil Additive**

**Control parameters**

**Occupational exposure limits**

Ingredient name	Exposure limits
Distillates (petroleum), solvent-refined heavy naphthenic	ACGIH TLV (United States, 3/2012). TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 6/2009). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist OSHA PEL (United States, 6/2010). TWA: 5 mg/m <sup>3</sup> 8 hours.

**Appropriate engineering controls:**

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Environmental exposure controls:**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

**Individual protection measures**

**Safety Data Sheet  
AP Pump Saver 195**

**Hygiene measures:**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection:**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side- shields.

**Skin protection**

**Hand protection:**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Body protection:**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection:**

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection:**

Use a properly fitted, air-purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

**Hydraulic Oil**

Chemical Name	ACGIH	OSHA	Other
Distillates, petroleum, hydrotreated heavy paraffinic	TWA: 5mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> as Oil Mist, if Generated	TWA: 5mg/m <sup>3</sup> as Oil Mist, if Generated	---
Distillates, petroleum, solvent-dewaxed heavy paraffinic	TWA: 5mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup> as Oil Mist, if Generated	TWA: 5mg/m <sup>3</sup> as Oil Mist, if Generated	---

**Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.**

**Engineering controls:**

If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

**Eye/Face Protection:**

The use of eye/face protection is not normally required; however, good industrial hygiene practice suggests the use of eye protection that meets or exceeds ANSI Z.87.1 whenever working with chemicals.

# Safety Data Sheet

## AP Pump Saver 195

### Skin/Hand Protection:

The use of skin protection is not normally required; however, good industrial hygiene practice suggests the use of gloves or other appropriate skin protection whenever working with chemicals. Suggested protective materials: Nitrile

### Respiratory Protection:

Where there is potential for airborne exposure above the exposure limit a NIOSH certified air purifying respirator equipped with R or P95 filters may be used.

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health (IDLH).

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

---

## SECTION 9. Physical and chemical properties

### Lucas Oil Additive

#### Appearance

Physical state:

Liquid. [Clear.]

Color:

Red.

Odor:

Petroleum

Odor threshold:

Not available.

pH:

Not available.

Melting point:

Not available.

Boiling point:

260°C (500°F)

Flash point:

Closed cup: 185°C (365°F)

Burning time:

Not applicable.

Burning rate:

Not applicable.

Evaporation rate:

Not available.

Flammability (solid, gas):

Not available.

Lower and upper explosive (flammable) limits:

Not available.

Vapor pressure:

Not available.

Vapor density:

Not available.

Relative density:

0.9254

Solubility:

Not available.

Solubility in water:

Negligible at 25°C

Partition coefficient: n- octanol/water:

Not available.

Auto-ignition temperature:

Not available.

Decomposition temperature:

Not available.

SADT:

Not available.

Viscosity:

Kinematic (100°C (212°F)): 0.43 cm<sup>2</sup>/s (43 cSt)

# Safety Data Sheet

## AP Pump Saver 195

### Hydraulic Oil

**Note:** Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

<b>Appearance:</b>	Light amber, Transparent
<b>Physical Form:</b>	Liquid
<b>Odor:</b>	Petroleum
<b>Odor Threshold:</b>	No data
<b>pH:</b>	Not applicable
<b>Vapor Density (air=1):</b>	>1
<b>Upper Explosive Limits (vol % in air):</b>	No data
<b>Lower Explosive Limits (vol % in air):</b>	No data
<b>Evaporation Rate (nBuAc=1):</b>	No data
<b>Particle Size:</b>	Not applicable
<b>Percent Volatile:</b>	No data
<b>Flammability (solid, gas):</b>	May Ignite
<b>Solubility in Water:</b>	Negligible
<b>Flash Point:</b>	> 374 °F / > 190 °C
<b>Test Method:</b>	Pensky-Martens Closed Cup (PMCC), ASTM D93, EPA 1010
<b>Initial Boiling Point/Range:</b>	No data
<b>Vapor Pressure:</b>	<1 mm Hg
<b>Partition Coefficient (n-octanol/water) (Kow):</b>	No data
<b>Melting/Freezing Point:</b>	No data
<b>Auto-ignition Temperature:</b>	No data
<b>Decomposition Temperature:</b>	No data
<b>Specific Gravity (water=1):</b>	0.86 - 0.88 @ 60°F (15.6°C)
<b>Bulk Density:</b>	7.2 - 7.3 lbs/gal
<b>Viscosity:</b>	7.5 - 9.5 cSt @ 100°C; 36 - 61 cSt @ 40°C
<b>Pour Point:</b>	< -51 to -33 °F / < -46 to -36 °C

---

## SECTION 10. Stability and reactivity

### Lucas Oil Additive

<b>Reactivity:</b>	No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability:</b>	The product is stable.
<b>Possibility of hazardous reactions:</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid:</b>	Excessive heat.
<b>Incompatible materials:</b>	Reactive or incompatible with the following materials: Strong oxidizers.
<b>Hazardous decomposition products:</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Hydraulic Oil

<b>Reactivity:</b>	Not chemically reactive.
<b>Chemical stability:</b>	Stable under normal ambient and anticipated conditions of use.

# Safety Data Sheet

## AP Pump Saver 195

<b>Possibility of hazardous reactions:</b>	Hazardous reactions not anticipated.
<b>Conditions to avoid:</b>	Extended exposure to high temperatures can cause decomposition. Avoid all possible sources of ignition.
<b>Incompatible materials:</b>	Avoid contact with strong oxidizing agents and strong reducing agents.
<b>Hazardous decomposition products:</b>	Not anticipated under normal conditions of use.

---

## SECTION 11. Toxicological information

### Lucas Oil Additive

#### Information on toxicological effects

##### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent- refined heavy naphthenic	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-

##### Irritation/Corrosion

<b>Skin:</b>	There is no data available.
<b>Eyes:</b>	There is no data available.
<b>Respiratory:</b>	There is no data available.

##### Sensitization

<b>Skin:</b>	There is no data available.
<b>Respiratory:</b>	There is no data available.

**Mutagenicity:** There is no data available.

**Carcinogenicity:** There is no data available.

**Reproductive toxicity:** There is no data available.

**Teratogenicity:** There is no data available.

**Specific target organ toxicity (single exposure):** There is no data available.

**Specific target organ toxicity (repeated exposure):** There is no data available.

**Aspiration hazard:** There is no data available.

**Information on the likely routes of exposure:** Routes of entry anticipated: Oral, Dermal, Inhalation.

##### Potential acute health effects

<b>Eye contact:</b>	No known significant effects or critical hazards.
<b>Inhalation:</b>	No known significant effects or critical hazards.
<b>Skin contact:</b>	No known significant effects or critical hazards.
<b>Ingestion:</b>	No known significant effects or critical hazards.

##### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact:</b>	No known significant effects or critical hazards.
<b>Inhalation:</b>	No known significant effects or critical hazards.
<b>Skin contact:</b>	No known significant effects or critical hazards.
<b>Ingestion:</b>	No known significant effects or critical hazards.

**Safety Data Sheet**  
**AP Pump Saver 195**

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

**Potential immediate effects:** No known significant effects or critical hazards.  
**Potential delayed effects:** No known significant effects or critical hazards

**Long term exposure**

**Potential immediate effects:** No known significant effects or critical hazards.  
**Potential delayed effects:** No known significant effects or critical hazards.

**Potential chronic health effects**

**General:** No known significant effects or critical hazards.  
**Carcinogenicity:** No known significant effects or critical hazards.  
**Mutagenicity:** No known significant effects or critical hazards.  
**Teratogenicity:** No known significant effects or critical hazards.  
**Developmental effects:** No known significant effects or critical hazards.  
**Fertility effects:** No known significant effects or critical hazards.

**Numerical measures of toxicity**

**Acute toxicity estimates:** There is no data available.

**Hydraulic Oil**

**Information on Toxicological Effects of Substance/Mixture Substance / Mixture**

Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Unlikely to be harmful		>5 mg/L (mist, estimated)
Dermal	Unlikely to be harmful		> 2 g/kg (estimated)
Oral	Unlikely to be harmful		> 5 g/kg (estimated)

**Aspiration Hazard:** Not expected to be an aspiration hazard.

**Skin Corrosion/Irritation:** Not expected to be irritating. Repeated exposure may cause skin dryness or cracking.

**Serious Eye Damage/Irritation:** Not expected to be irritating.

**Skin Sensitization:** No information available on the mixture, however none of the components have been classified for skin sensitization (or are below the concentration threshold for classification).

**Respiratory Sensitization:** No information available.

**Specific Target Organ Toxicity (Single Exposure):** No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

**Specific Target Organ Toxicity (Repeated Exposure):** No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

# Safety Data Sheet

## AP Pump Saver 195

<b>Carcinogenicity:</b>	No information available on the mixture, however none of the components have been classified for carcinogenicity (or are below the concentration threshold for classification).
<b>Germ Cell Mutagenicity:</b>	No information available on the mixture, however none of the components have been classified for germ cell mutagenicity (or are below the concentration threshold for classification).
<b>Reproductive Toxicity:</b>	No information available on the mixture, however none of the components have been classified for reproductive toxicity (or are below the concentration threshold for classification).

### Information on Toxicological Effects of Components

#### Lubricant Base Oil (Petroleum)

##### ***Carcinogenicity:***

The petroleum base oils contained in this product have been highly refined by a variety of processes including severe hydrocracking/hydroprocessing to reduce aromatics and improve performance characteristics. All of the oils meet the IP-346 criteria of less than 3 percent PAH's and are not considered carcinogens by NTP, IARC, or OSHA.

---

## SECTION 12. Ecological information

### Lucas Oil Additive

<b>Toxicity</b>	There is no data available.
<b>Persistence and degradability</b>	There is no data available.
<b>Bioaccumulative potential</b>	There is no data available.
<b>Mobility in soil</b>	
<b>Soil/water partition coefficient (<math>K_{oc}</math>):</b>	There is no data available.
<b>Other adverse effects:</b>	No known significant effects or critical hazards.

### Hydraulic Oil

<b>GHS Classification:</b>	No classified hazards
<b>Toxicity:</b>	All acute aquatic toxicity studies on samples of lubricant base oils show acute toxicity values greater than 100 mg/L for invertebrates, algae and fish. These tests were carried out on water accommodated fractions and the results are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions.
<b>Persistence and Degradability:</b>	The hydrocarbons in this material are not readily biodegradable, but since they can be degraded by microorganisms, they are regarded as inherently biodegradable.

# Safety Data Sheet

## AP Pump Saver 195

### Bioaccumulative Potential:

Log Kow values measured for the hydrocarbon components of this material are greater than 5.3, and therefore regarded as having the potential to bioaccumulate. In practice, metabolic processes may reduce bioconcentration.

### Mobility in Soil:

Volatilization to air is not expected to be a significant fate process due to the low vapor pressure of this material. In water, base oils will float and spread over the surface at a rate dependent upon viscosity. There will be significant removal of hydrocarbons from the water by sediment adsorption. In soil and sediment, hydrocarbon components will show low mobility with adsorption to sediments being the predominant physical process. The main fate process is expected to be slow biodegradation of the hydrocarbon constituents in soil and sediment.

### Other adverse effects:

None anticipated.

---

## SECTION 13. Disposal considerations

### Lucas Oil Additive

#### Disposal methods:

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Hydraulic Oil

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations. This material, if discarded as produced, would not be a federally regulated RCRA "listed" hazardous waste and is not believed to exhibit characteristics of hazardous waste. See Sections 7 and 8 for information on handling, storage and personal protection and Section 9 for physical/chemical properties. It is possible that the material as produced contains constituents which are not required to be listed in the SDS but could affect the hazardous waste determination. Additionally, use which results in chemical or physical change of this material could subject it to regulation as a hazardous waste. This material under most intended uses would become "Used Oil" due to contamination by physical or chemical impurities. Whenever possible, Recycle used oil in accordance with applicable federal and state or local regulations. Container contents should be completely used and containers should be emptied prior to discard.

**Safety Data Sheet  
AP Pump Saver 195**

**SECTION 14. Transport information**

**Lucas Oil Additive**

	<b>DOT Classification</b>	<b>IMDG</b>	<b>IATA</b>
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

**Special precautions for user:**

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:**

Not available.

**Hydraulic Oil**

**U.S. Department of Transportation (DOT)**

**Shipping Description:**

Not regulated

**Note:**

If shipped by land in a packaging having a capacity of 3,500 gallons or more, the provisions of 49 CFR, Part 130 apply. (Contains oil)

**International Maritime Dangerous Goods (IMDG)**

**Shipping Description:**

Not regulated

**Note:**

U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 25.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:**

Not applicable

**International Civil Aviation Org. / International Air Transport Assoc. (ICAO/IATA)**

**UN/ID #:**

Not regulated

**Note:**

U.S. DOT compliance requirements may apply. See 49 CFR 171.22, 23 & 24.

	<b>LTD. QTY</b>	<b>Passenger Aircraft</b>	<b>Cargo Aircraft Only</b>
Packaging Instruction #:	---	---	---
Max. Net Qty. Per Package:	---	---	---

---

## SECTION 15. Regulatory information

### Lucas Oil Additive

<b>U.S. Federal regulations:</b>	TSCA 8(a) CDR Exempt/Partial exemption: All components are listed or exempted. United States inventory (TSCA 8b): All components are listed or exempted.
<b>Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs):</b>	Not listed
<b>Clean Air Act Section 602 Class I Substances:</b>	Not listed
<b>Clean Air Act Section 602 Class II Substances:</b>	Not listed
<b>DEA List I Chemicals (Precursor Chemicals):</b>	Not listed
<b>DEA List II Chemicals (Essential Chemicals):</b>	Not listed
<b>SARA 302/304 Composition/information on ingredients:</b>	No products were found.
<b>SARA 304 RQ:</b>	Not applicable.
<b>SARA 311/312 Classification:</b>	Not applicable.
<b>Composition/information on ingredients:</b>	No products were found.
<b>State regulations</b>	
<b>Massachusetts:</b>	None of the components are listed.
<b>New York:</b>	None of the components are listed.
<b>New Jersey:</b>	The following components are listed: Distillates (petroleum), solvent-refined heavy naphthenic
<b>Pennsylvania:</b>	None of the components are listed.
<b>California Prop. 65:</b>	No products were found.
<b>International regulations</b>	
<b>International lists:</b>	Australia inventory (AICS): All components are listed or exempted. China inventory (IECSC): All components are listed or exempted. Japan inventory: Not determined. Korea inventory: All components are listed or exempted. Malaysia Inventory (EHS Register): Not determined. New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. Taiwan inventory (CSNN): Not determined.

# Safety Data Sheet

## AP Pump Saver 195

**Chemical Weapons Convention List  
Schedule I Chemicals:** Not listed

**Chemical Weapons Convention List  
Schedule II Chemicals:** Not listed

**Chemical Weapons Convention List  
Schedule III Chemicals:** Not listed

### Hydraulic Oil

#### **CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds):**

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

#### **CERCLA/SARA - Section 311/312 (Title III Hazard Categories)**

**Acute Health Hazard:** No  
**Chronic Health Hazard:** No  
**Fire Hazard:** No  
**Pressure Hazard:** No  
**Reactive Hazard:** No

#### **CERCLA/SARA - Section 313 and 40 CFR 372:**

This material contains the following chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372:

<b>Chemical Name</b>	<b>Concentration<sup>1</sup></b>	<b>de minimis</b>
Zinc Compound(s)	<2	1.0%

#### **EPA (CERCLA) Reportable Quantity (in pounds):**

This material does not contain any chemicals with CERCLA Reportable Quantities.

#### **California Proposition 65:**

This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65.

#### **International Hazard Classification**

##### **Canada:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the Regulations.

##### **WHMIS Hazard Class:**

none

#### **National Chemical Inventories**

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA. All components are either on the DSL, or are exempt from DSL listing requirements.

**U.S. Export Control Classification Number:** EAR99

---

## **SECTION 16. Other information**

### **Lucas Oil Additive**

#### **Hazardous Material Information System (U.S.A.)**

**Health: 0      Flammability: 1      Physical hazards: 0**

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

#### **National Fire Protection Association (U.S.A.)**

**Health: 0      Flammability: 1      Instability: 0**

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### **History**

**Date of issue mm/dd/yyyy:** 06/15/2013  
**Version:** 1  
**Revised Section(s):** Not applicable.  
**Prepared by:** KMK Regulatory Services Inc.

#### **Key to abbreviations:**

ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

# Safety Data Sheet

## AP Pump Saver 195

### Hydraulic Oil

Date of Issue:	Previous Issue Date:	SDS Number:	Status:
5-13-15	26-Jul-2013	16 11 01 A	FINAL

#### **Revised Sections or Basis for Revision:**

Distributor (Section 1); Toxicological (Section 11)

#### **Guide to Abbreviations:**

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

#### **Disclaimer of Expressed and implied Warranties:**

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.