



## Safety Data Sheet Spetec PUR H200

---

### SECTION 1: Identification

#### Product identifier

Product name Spetec PUR H200

#### Recommended use of the chemical and restrictions on use

Water activated semi-rigid polyurethane foam injection resin.

#### Supplier's details

Name Alchemy-Spetec  
Address 4508 Bibb Blvd  
Tucker GA 30084

Telephone (404) 618-0438

#### Emergency phone number(s)

Call CHEMTREC Day or Night  
1-800-424-9300 / +1 703-527-3887

---

### SECTION 2: Hazard identification

#### Classification of the substance or mixture

#### GHS classification in accordance with: OSHA (29 CFR 1910.1200)

- Acute toxicity, inhalation, Cat. 4
- Carcinogenicity, Cat. 2
- Sensitization, respiratory, Cat. 1
- Eye damage/irritation, Cat. 2A
- Skin corrosion/irritation, Cat. 2
- Sensitization, skin, Cat. 1
- Specific target organ toxicity (repeated exposure), Cat. 2
- Specific target organ toxicity (single exposure), Cat. 3

#### GHS label elements, including precautionary statements

#### Pictogram



#### Signal word

Danger

**Safety Data Sheet**  
**Spetec PUR H200**

**Hazard statement(s)**

H315 Causes skin irritation  
 H317 May cause an allergic skin reaction  
 H319 Causes serious eye irritation  
 H332 Harmful if inhaled  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled  
 H335 May cause respiratory irritation  
 H351 Suspected of causing cancer  
 H373 May cause damage to organs [Respiratory Tract] through prolonged or repeated exposure if inhaled.

**Precautionary statement(s)**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P284 [In case of inadequate ventilation] wear respiratory protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P312 Call a POISON CENTER or doctor if you feel unwell.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P363 Wash contaminated clothing before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

No data available.

---

**SECTION 3: Composition/information on ingredients**

**Mixtures**

**Hazardous components**

Component	Concentration
4,4'-Methylenediphenyl diisocyanate (MDI) (CAS no.: 101-68-8)	20 - 60 % (weight)*
4,4' Diphenylmethanediisocyanate, isomere, homologue and mixtures (pMDI) (CAS no.: 9016-87-9)	20 - 60 % (weight)*

**Trade secret statement (OSHA 1910.1200(i))**

\*The specific chemical identities and/or actual concentrations or actual concentration ranges for one or more listed components are being withheld as trade secrets under the US regulation 29 CFR 1910.1200(i).

## **SECTION 4: First-aid measures**

### **Description of necessary first-aid measures**

General advice	First aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.
If inhaled	<p>If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc.). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.</p> <p>Acute and delayed symptoms: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.</p>
In case of skin contact	<p>Wash with plenty of soap and water. Call a poison center or doctor if irritation develops or persists. Take off contaminated clothing and wash it before reuse.</p> <p>Acute and delayed symptoms and effects: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.</p>
In case of eye contact	<p>Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Product reacts with moisture in eye! Immediately seek medical attention. Suitable emergency eye wash facility should be immediately available.</p> <p>Acute and delayed symptoms and effects: Causes serious eye damage. Product reacts with moisture in eye! Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.</p>
If swallowed	<p>SEEK IMMEDIATE MEDICAL ATTENTION! DELAYED TREATMENT MAY RESULT IN FATALITY. Do Not Induce Vomiting. Rinse mouth out with water. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.</p>

### **Most important symptoms/effects, acute and delayed**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

### **Indication of immediate medical attention and special treatment needed, if necessary**

Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

## **SECTION 5: Fire-fighting measures**

### **Suitable extinguishing media**

Use water fog, carbon dioxide or dry chemical. Water contamination in a closed container or a confined area is to be avoided due to the exothermic CO<sub>2</sub> evolution upon water contamination.

### **Specific hazards arising from the chemical**

During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Exposure to heated diisocyanate can be extremely dangerous

Fire or intense heat will decompose the product into CO<sub>2</sub>, CO, Hydrogen Cyanide, Oxides of Nitrogen, Isocyanates, Isocyanic Acid, and dense black smoke.

### **Special protective actions for fire-fighters**

Do not scatter material with high pressure water streams. Firefighters should wear NFPA compliant structural firefighting protective equipment, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Exposure to heated diisocyanate can be extremely dangerous. Closed container may forcibly rupture under extreme heat or when contents are contaminated with water (CO<sub>2</sub> formed). Use cold-water spray to cool fire-exposed containers to minimize the risk of rupture. Large fires can be extinguished with large volumes of water applied from a safe distance, since reaction between water and hot diisocyanate can be vigorous.

### **Further information**

Use water spray to cool unopened containers.

---

## **SECTION 6: Accidental release measures**

### **Personal precautions, protective equipment and emergency procedures**

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Keep upwind of spill. Spilled material may cause a slipping hazard. Ventilate area of leak or spill. Where exposure level is known, wear approved respirator suitable for the level of exposure. If exposure level is unknown, wear approved, positive pressure, self-contained respirator. In addition to the protective clothing in section 8, wear impermeable boots.

### **Environmental precautions**

Prevent unreacted product from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

### **Methods and materials for containment and cleaning up**

Remove sources of ignition. Stop and contain / dam the spill. Absorb spill with inert material (vermiculite / diatomaceous earth). Shovel material into appropriate container for disposal. Do not place in sealed containers as it may still be reacting and could rupture.

---

## **SECTION 7: Handling and storage**

### **Precautions for safe handling**

Do not breathe vapors, mists, or dusts. Use adequate ventilation to keep airborne isocyanate levels below the exposure limits. Wear respiratory protection if material is heated, sprayed, used in a confined space, or if the exposure limit is exceeded. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent overexposure from inhalation. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapor or spray mist. Avoid contact with skin and eyes. Wear appropriate eye and skin protection.

# Safety Data Sheet

## Spetec PUR H200

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Wash thoroughly after handling. Do not breathe smoke and gases created by overheating or burning this material. Decomposition products can be highly toxic and irritating. Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected.

### Conditions for safe storage, including any incompatibilities

Keep in manufacturer's sealed nitrogen packed pail. Maintain storage temperatures between 65°F to 86°F (18°C to 30°C). Store in a dry place. Protect from atmospheric moisture. Do not store product contaminated with water to prevent potential hazardous reaction. See Section 10 for more specific information.

### Specific end use(s)

See the technical data sheet on this product for further information.

---

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### CAS: 101-68-8

Methylene bisphenyl isocyanate (MDI)

ACGIH: 0.005 ppm TLV® inhalation; Cal/OSHA: 0.005 ppm PEL inhalation; NIOSH: 0.05 mg/m<sup>3</sup>, (C) 0.2 mg/m<sup>3</sup> [10-min] REL inhalation; OSHA: (C) 0.02 ppm PEL inhalation; (C) 0.2 mg/m<sup>3</sup> PEL inhalation

### Appropriate engineering controls

Use only with adequate ventilation. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure. Local exhaust ventilation may be necessary for some operations.

### Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Safety glasses. If splash hazard, wear face shield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Ensure that eyewash stations and/or safety showers are close to the workstation location if working with concentrated product.

#### Skin protection

Wear protective gloves. Consult manufacturer specifications for further information. In cured form, the product is difficult to remove from skin and hair.

#### Body protection

Wear protective clothing. Clothing with full length sleeves and pants should be worn. Selection of additional items such as face shield, boots, apron, or full body suit will depend on the task.

#### Respiratory protection

Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved air-purifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

#### Environmental exposure controls

Do not let uncured product enter drains.

## **SECTION 9: Physical and chemical properties**

### **Information on basic physical and chemical properties**

Appearance/form (physical state, color, etc.)	Dark brown liquid
Odor	Slightly musty odor
Odor threshold	No data available.
pH	No data available.
Melting point/freezing point	<- 4°F (<- 20°C)
Initial boiling point and boiling range	No data available.
Flash point	293°F (145°C)
Evaporation rate	No data available.
Flammability (solid, gas)	Non-flammable
Upper/lower flammability limits	No data available.
Upper/lower explosive limits	No data available.
Vapor pressure	0.0006 mm Hg @ 40°C
Vapor density	No data available.
Relative density	9.6-9.9 lbs/gal
Solubility(ies)	No data available.
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	No data available.
Decomposition temperature	<212°F(<100°C)
Viscosity	No data available.
Explosive properties	No data available.
Oxidizing properties	No data available.

---

## **SECTION 10: Stability and reactivity**

### **Reactivity**

Contact with moisture or temperatures above 350° F (177° C) will cause polymerization.

### **Chemical stability**

Stable under recommended storage conditions. See Storage, Section 7.

### **Possibility of hazardous reactions**

Can occur. Exposure to elevated temperatures can cause product to decompose and generate gas. This can cause pressure build-up and/or rupturing of closed containers. Polymerization can be catalyzed by: Strong bases or water. During normal polymerization CO<sub>2</sub> is produced.

### **Conditions to avoid**

Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Pressure build-up can be rapid. Avoid moisture. Material reacts slowly with water, releasing carbon dioxide which can cause pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.

### **Incompatible materials**

Amines, Strong Bases, Alcohols, Copper Alloys, Liquid Chlorine. Water- until ready to react

### **Hazardous decomposition products**

Fire or intense heat will decompose the product into CO<sub>2</sub>, CO, Hydrogen Cyanide, Oxides of Nitrogen, Isocyanates, Isocyanic Acid, and dense black smoke.

## **SECTION 11: Toxicological information**

### **Information on toxicological effects**

#### **Acute toxicity**

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Typical for this family of materials.

LD50, rat > 10,000 mg/kg

#### **Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Typical for this family of materials.

LD50, Rabbit, > 9,400 mg/kg

#### **Acute inhalation toxicity**

At room temperature, vapors are minimal due to low volatility. However, certain operations may generate vapor or mist concentrations sufficient to cause respiratory irritation and other adverse effects. Such operations include those in which the material is heated, sprayed or otherwise mechanically dispersed such as drumming, venting or pumping. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Decreased lung function has been associated with overexposure to isocyanates.

LC50, Rat, 4 Hour, dust/mist, 0.49 mg/l

For similar material(s): 4,4'-Methylenediphenyl diisocyanate (CAS 101-68-8).

LC50, Rat, 1 Hour, Aerosol, 2.24 mg/l

For similar material(s): 2,4'-Diphenylmethane diisocyanate (CAS 5873-54-1).

LC50, Rat, 4 Hour, Aerosol, 0.387 mg/l

#### **Skin corrosion/irritation**

Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

#### **Serious eye damage/irritation**

Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Respiratory or skin sensitization**

May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **Germ cell mutagenicity**

No data available.

#### **Carcinogenicity**

IARC: 4,4' diphenylmethanediisocyanate, isomere, homologue and mixtures. Result: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Isocyanic acid, polymethylenepolyphenylene ester)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

No data available.

# Safety Data Sheet

## Spetec PUR H200

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

May cause damage to organs [Respiratory Tract] through prolonged or repeated exposure if inhaled.

### Aspiration hazard

Based on physical properties, not likely to be an aspiration hazard.

---

## SECTION 12: Ecological information

### Toxicity

No data available on product

Components:

4,4'-Methylenebis(phenyl isocyanate)  
EC50 - Daphnia magna (water flea) - 0.35 mg/ - 24 hr

### Persistence and degradability

No data available on product

In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable.

### Bioaccumulative potential

No data available on product

Components:

4,4'-Methylenebis(phenyl isocyanate)  
- Cyprinus carpio (Carp) - 0.0008 mg/l - 28 d  
Result: Bioconcentration factor (BCF): 92

### Mobility in soil

No data available.

### Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### Other adverse effects

No data available.

---

## SECTION 13: Disposal considerations

### Disposal of the product

Disposal should be in accordance with applicable Federal, State and local laws and regulations. Local regulations may be more stringent than State or Federal requirements.

### Disposal of contaminated packaging

Dispose of as unused product.

Empty Container Precautions:

Empty containers retain product residue; observe all precautions for product. Do not heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed. Do not reuse without thorough



# Safety Data Sheet

## Spetec PUR H200

commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed prior to disposal. Dispose of per local, state and federal guidelines as required by your specific local. This product in its cured foam state is inert and non-toxic.

---

### SECTION 14: Transport information

#### DOT (US)

Not regulated

Reportable quantity (RQ): 5000 lb (4,4'- Diphenylmethane Diisocyanate)

#### IMDG

Not regulated

#### IATA

Not regulated

---

### SECTION 15: Regulatory information

#### Safety, health and environmental regulations specific for the product in question

##### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

##### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

##### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

##### Massachusetts Right To Know Components

Chemical name: Polymeric diphenylmethane diisocyanate

CAS number: 9016-87-9

Chemical name: MDI

CAS number: 101-68-8

##### New Jersey Right To Know Components

Common name: METHYLENE DIPHENYL DIISOCYANATE (POLYMERIC)

CAS number: 9016-87-9

Common name: METHYLENE BISPHENYL ISOCYANATE

CAS number: 101-68-8

##### Pennsylvania Right To Know Components

Chemical name: Benzene, 1,1'-methylenebis[4-isocyanato-

CAS number: 101-68-8

##### Canadian Domestic Substances List (DSL)

Chemical name: Isocyanic acid, polymethylenepolyphenylene ester

CAS: 9016-87-9

# Safety Data Sheet

## Spetec PUR H200

Chemical name: Benzene, 1,1'-methylenebis[4-isocyanato-  
CAS: 101-68-8

---

### SECTION 16: Other information

#### Further information/disclaimer

DISCLAIMER: The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigation to determine the suitability of information for their particular purposes. In no event shall Alchemy-Spetec be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, whatsoever arising, even if Alchemy-Spetec has been advised of the possibility of such damages.